

QuietMOD H/H-52 PANEL DESCRIPTION:

- PANEL IS 4" THICK WITH 16 GAUGE SOLID SKIN ON ONE SIDE AND A 12 GAUGE SOLID SKIN ON THE OTHER SIDE
- ENTIRE PANEL IS CONSTRUCTED WITH "PAINT READY" GALVANNEAL A-60 STEEL WITH INTERNAL STIFFENERS EVERY 24" O.C.
- FACE SHEETS ARE SPOT WELDED TO THE PANEL FRAMING CHANNEL
- ALL STIFFENERS AND CHANNEL FRAMING ARE FORMED FROM A MINIMUM OF 18 GA. STEEL
- ACOUSTIC FILL IS NON-COMBUSTIBLE, SOUND ABSORBING FIBERGLASS OR MINERAL WOOL
- PRIME PAINTING OR FACTORY FINISH PAINTING IS AVAILABLE
- PANEL WEIGHS 8.0 lbs./sq.ft.


**SOUND TRANSMISSION LOSS, dB**

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QuietMOD H/H-52 PANEL	37	43	47	53	54	57	52

\*All testing conducted by Riverbank Acoustical Laboratories  
 \*All data in accordance with ASTM E90-99 and E413-87

REVISIONS		DESCRIPTION	DATE	BY

DESCRIPTION		QuietMOD H/H 52 ACOUSTIC PANEL	
CUSTOMER		DRAWN BY	MAH
SCALE		SHEET	
DATE		DRAWING NO.	QM-HH-52


**Noise Barriers, LLC**  
 872 S. Milwaukee Ave., #139  
 Libertyville, IL 60048  
 Phone: (800) 386-6800  
 Fax: (847) 362-7319  
[www.noisebarriers.com](http://www.noisebarriers.com)