



QuietSwing[®]

QuietFold BI-PARTING DOOR SERIES



APPLICATIONS

- Theatre back-of-stage
- Studio partitions
- Studio equipment doors
- Production space
- Churches
- Test facilities
- Schools
- Power generation facilities



QuietFold BI-PARTING DOOR SERIES

MOUNTS TO
DOOR JAMB
ONLY



TYPICAL
HARDWARE CAN
BE USED



QUIETSWING
DOUBLE
SEAL



FEATURES:

- 4- or 6-hinge leaves
- Doors are mounted to jambs only
- Both sides can be fully opened with minimal floor space being occupied
- Any combination of opening just one, two, or all leaves for flexibility of operation
- All swing with the ease of our standard QuietSwing doors
- Design based on the long-standing success of our double seal QuietSwing doors
- Typical hardware can be used
- Powder-coat or veneer finishes

ACOUSTICAL PERFORMANCE DATA SOUND TRANSMISSION LOSS DATA, dB

1/3 Octave Band Center Frequency, Hz	125	250	500	1K	2K	4K	STC
QS-50, 2 ^{1/2"} Thick - 10.1 PSF	37	42	50	49	51	55	50
QS-52, 2 ^{1/2"} Thick - 10.5 PSF	40	44	50	53	54	56	52
QS-54, 3 ^{1/2"} Thick - 18.3 PSF	37	47	52	54	55	60	54

These are an NIC 62 and 70. Field testing results may vary due to Room Size, Configuration, and Room Acoustics.

SEE OUR BI-PARTING DOORS IN ACTION



NOISE BARRIERS.

