



# H/S/P-43b PANEL

## QuietMOD H/S/P-43 PANEL DESCRIPTION:

- PANEL IS 4" THICK WITH SOLID SKIN ON ONE SIDE AND A PERFORATED SKIN ON THE OTHER.
- ENTIRE PANEL IS CONSTRUCTED WITH "PAINT READY" A-60 GALVANNEAL OR G-90 GALVANIZED STEEL
- FACE SHEETS ARE SPOT WELDED TO THE PANEL FRAMING CHANNEL
- ALL STIFFENERS AND CHANNEL FRAMING ARE FORMED FROM A MINIMUM OF 18 GA. STEEL

## SOUND TRANSMISSION LOSS, dB

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QuietMOD H/S/P-43 PANEL	27	32	40	50	58	64	43

\*All testing conducted by Riverbank Acoustical Laboratories  
 \*All data in accordance with ASTM E90-99 and E413-87

weight = 11.13 lbs/sq.ft.

Riverbanks Test No. TL14-434  
 Test Date: 12-5-2014

### PROPRIETARY

THIS DESIGN AND DRAWING IS THE EXCLUSIVE PROPERTY OF NOISE BARRIERS, LLC. AND IS SUBMITTED AS CONFIDENTIAL INFORMATION IN CONNECTION WITH YOUR INQUIRY. IT MUST NOT BE USED FOR ANY OTHER PURPOSES, NOR CAN IT BE COPIED OR LOANED WITHOUT WRITTEN PERMISSION. UPON REQUEST IT MUST BE RETURNED IMMEDIATELY.

QUIETMOD H/S/P-43  
 ACOUSTIC WALL  
 PANEL DETAIL

PROJECT:		TYPE:	
SUBMITTED BY:	DATE:	ISSUE:	
APPROVED BY:	DATE:	PROJECT No.:	
PROJ. MGR.	SHEET:		



**NOISE BARRIERS**  
 401 AIRPORT DRIVE  
 NORTH AURORA, IL 60532  
 Phone: (847) 843-0500  
 Fax: (847) 843-0501  
 www.noisebarriers.com